

XYLENE

SOLVENT FOR COATINGS AND SEALERS

Xylene is for use as a diluent for acrylic coatings and as a general-purpose solvent.

Type:	100% volatile solvent
Toxicity:	Harmful if swallowed
VOC's	N/A
Flammability:	Flammable
Color:	Colorless
Odor:	Solvent
Composition:	100% volatile aromatic solvents.

NOTE: CAREFULLY READ ALL DIRECTIONS, NOTES AND CAUTIONS PRIOR TO USE. ONLY USE THIS PRODUCT AS DIRECTED ON THE LABEL. DO NOT SPREAD THIS PRODUCT OVER SURFACE AREAS GREATER THAN 1 SQ. FOOT BECAUSE OF FIRE AND HEALTH RISKS COULD INCREASE RAPIDLY.

PRODUCT HIGHLIGHTS

- 100% volatile: Xylene is completely volatile and leaves no residue.
- Clean and colorless: Xylene does not affect the color or clarity of the seal.
- A range of evaporation rates: Xylene is fast evaporating and dries very fast at all temperatures
- Safety: Xylene is extremely flammable and must be used with caution.

PRODUCT USES

Use Xylene to reduce solids content of sealers for greater penetration or to clean equipment and brushes and well as spraying over an acrylic sealer that shows blushing or uneven surfaces to relax the surface and re-establish a smooth clear surface.